

2.11 PRIMAFLEX UNI 3000HT

Temperature range -55°C to +180°C



Description

Flexible, high-temperature resistant hose made of polyurethane coated on both sides.

Well suited for conveying media at temperatures of up to +180 °C.

Flame retardant: M1 & UL94 VTM-0
California Proposal 65 conform

Properties

- flexible
- light
- good compressibility
- good cold flexibility
- good resistance to alkalis, acids and chemicals
- flame retardant according to UL94VTM-0 &M1
- California Proposal 65 conform

Chemical resistance

- Ammonia Oils
- Diesel
- Oils

Applications

- Exhaust air systems
- Extraction arm
- Plant construction
- Building drying
- Building drying
- Ventilation
- Ventilation
- Air conditioning and ventilation technology
- Kitchen extractor fan
- Ventilation hose
- Ventilation technology
- Mechanical engineering
- Welding gas extraction

Length

Standard length: 10-20 m. Other lengths on request.

Further information

Color: Dark grey

TECHNICAL SPECIFICATIONS

Inner-Ø (mm)	Bending radius (mm)	Pressure (bar)	Vacuum (bar)	Weight (kg/m)	Length (m)	Article-No.
50	35	0,8	0,2	0,13	10 - 20	
63	42	0,8	0,16	0,17	10 - 20	
70	49	0,7	0,14	0,2	10 - 20	
76	53	0,6	0,1	0,22	10 - 20	
80	56	0,6	0,1	0,24	10 - 20	
102	70	0,5	0,09	0,31	10 - 20	
127	88	0,5	0,08	0,38	10 - 20	
152	105	0,5	0,06	0,45	10 - 20	
180	130	0,2	0,05	0,65	10 - 20	
203	140	0,2	0,05	0,73	10 - 20	
254	175	0,1	0,04	0,92	10 - 20	
305	210	0,06	0,03	1,11	10 - 20	
357	245	0,05	0,02	1,3	10 - 20	
408	280	0,04	0,02	1,5	10 - 20	
510	350	0,02	0,01	1,9	10 - 20	